

Product Features


- low pressure loss
- wetted metal parts made from dezincification-free and corrosion-resistant gunmetal, resistant against aggressive water
- full bore
- female pipe thread
- removable inner top part TOP-ENTRY, with EPDM gasket body and gunmetal ball
- operating handle 90° rotatable
- free from dead spots

Standards and Approvals

- DVGW approval
- WRAS approval
- KIWA UK water regulation 4 approval
- plastic parts with KTW and W 270 approval
- according to DVGW worksheet W 570
- according to accepted materials list from German environmental agency
- up to DN 32 soundproofing certification according to DIN EN ISO 3822 Class 1
- DIN EN 13828
- ÜA-Reg.-Nr. R-15.2.3-21-17048, WIEN-ZERT

Technical Data

- pressure rating PN 16
- max. operating temperature 90 °C



part no.	DN	A1	D1 (mm)	H1 (mm)	H2 (mm)	L1 (mm)	T1 (mm)	kg
3850001500	15	Rp 1/2	90	55,5	25	84	14,5	0,498
3850002000	20	Rp 3/4	90	55,5	25	90	16,5	0,591
3850002500	25	Rp 1	90	58,5	28	99	18	0,829

accessory

insulation shell for quarter turn stop valves and CONTROL-PLUS sensors, figure 471 19